

DATASHEET F-106CI

IN-FLOW 'High-Flow' F-106CI

Industrial Style Mass Flow Meter for High Gas Flow



Industrial Style Gas Mass Flow Meters for high flow rates

Bronkhorst® model F-106CI Mass Flow Meters (MFMs) are suited for precise measurement of flow ranges between 2...100 m³_n/h and 20...1000 m³_n/h at operating pressures up to 40 bar. The MFM consists of a thermal mass flow sensor and a microprocessor based pc-board with signal and fieldbus conversion and a PID controller for optional mass flow control by means of a separately mounted control valve. The IN-FLOW model is of rugged design (IP65) for use in industrial environments or even Zone 2 hazardous areas, with optional ATEX Cat. 3 or FM Class I, Div. 2 approval.

IN-FLOW series are equipped with a digital pc-board, offering high accuracy, excellent temperature stability and fast response. The main digital pc-board contains all of the general functions needed for measurement and control. In addition to the standard RS232 output the instruments also offer analog I/O. As an option, an on-board interface can be mounted to provide CANopen®, DeviceNet™, EtherCAT®, PROFIBUS DP, PROFINET, Modbus RTU, ASCII or TCP/IP, EtherNet/IP, POWERLINK or FLOW-BUS protocols.

Technical specifications

Measurement / control system

| | |
|--|--|
| Flow range (intermediate ranges available) | min. 2...100 m ³ _n /h max. 20...1000 m ³ _n /h (based on N ₂) |
| Accuracy (incl. linearity) (based on actual calibration) | ± 1 % FS |
| Repeatability | < 0,2 % RD |
| Turndown ratio | 1:50 |
| Multi fluid capability | Storage of max. 8 calibration curves |
| Response time (sensor) | typical: 0,5 sec. |
| Operating temperature | -10 ...+70 °C for ATEX cat. 3 and FM Class 1 Div 2 : 0...50°C |
| Temperature sensitivity | zero: < 0,05% FS/°C; span: < 0,05% Rd/°C |
| Pressure sensitivity | 0,1% Rd/bar typical N ₂ ; 0,01% Rd/bar typical H ₂ |
| Leak integrity, outboard | tested < 2 x 10 ⁻⁹ mbar l/s He |
| Attitude sensitivity | max. error at 90° off horizontal 0,2% FS at 1 bar, typical N ₂ |
| Warm-up time | 30 min. for optimum accuracy 2 min for accuracy ± 2% FS |

Mechanical parts

| | |
|-------------------------|------------------------------------|
| Material (wetted parts) | stainless steel 316L or comparable |
|-------------------------|------------------------------------|

Mechanical parts

| | | | | |
|----------------------|---|--|--|--|
| Pressure rating (PN) | up to 40 bar abs (PN10, 16, 40); for hazardous gases such as O ₂ , H ₂ , etc. do not exceed operating pressure of 10 bar; for higher pressure select a flanged type MFM, series F-107/F-117. | | | |
| Process connections | Wafer type, for mounting between flanges according to DIN DN80 or ANSI 3" | | | |
| Seals | standard: Viton®; options: EPDM, Kalrez® (FFKM) | | | |
| Weight | 6,8 kg | | | |
| Ingress protection | IP65 | | | |

Electrical properties

| | | | | |
|------------------------|--|----------------|----------------|--------------------|
| Power supply | +15 ... 24 Vdc | | | |
| Max. power consumption | Supply | at voltage I/O | at current I/O | extra for fieldbus |
| | 15 V | 95 mA | 125 mA | <75 mA |
| | 24 V | 65 mA | 85 mA | <50 mA |
| Analog output | 0...5 (10) Vdc or 0 (4)...20 mA (sourcing output) | | | |
| Digital communication | standard: RS232; options: CANopen®, DeviceNet™, EtherCAT®, PROFIBUS DP, PROFINET, Modbus RTU, ASCII or TCP/IP, EtherNet/IP, POWERLINK or FLOW-BUS | | | |

Electrical connection

| | |
|---|---|
| Analog/RS232 | 8 DIN (male); |
| PROFIBUS DP | bus: 5-pin M12 (female); power: 8 DIN (male); |
| CANopen® / DeviceNet™ | 5-pin M12 (male); |
| FLOW-BUS/Modbus-RTU/ASCII | 5-pin M12 (male); |
| Modbus TCP / EtherNet/IP / POWERLINK | bus: 2 x 5-pin M12 (female) (in/out); power: 8 DIN (male); |
| EtherCAT®/ PROFINET | bus: 2 x 5-pin M12 (female) (in/out); power: 8 DIN (male) |
| IEC 61010-1 | IEC-61010-1:2010 including national deviations for UL (61010-1:2012) and CSA (C22.2 No. 61010-1-12) |

Control valve options

External actuator options to be connected to the controller

Ex-proof specifications

Approvals / certificates

Technical specifications subject to change without notice.

For dimensional drawings and hook-up diagrams please visit the [product page](#) on our [website](#)

Recommended accessories



E-8000 SERIES

Digital Readout / Control Systems

Bright, wide angle, 1.8" display (TFT technology)
User friendly operation, menu driven with 4 push buttons



BRIGHT SERIES

Compact Local R/C Module

Bright, wide angle, 1.8" display
User friendly operation
Indication/operation/configuration



PIPS SERIES

Plug-in Power Supply

For lab-style or industrial devices
Interchangeable plugs (Euro, UK, USA, Australian, IEC) for mains connection

Related products



IN-FLOW 'HIGH-FLOW' F-106BI

Min. flow 1 ... 50 m3n/h
Max. flow 10 ... 500 m3n/h
Pressure rating up to 40 bar
Wafer type connection (DIN/ANSI)
Rugged IP65 housing



IN-FLOW 'HIGH-FLOW' F-106DI

Min. flow 3,6 ... 180 m3n/h
Max. flow 36 ... 1800 m3n/h
Pressure rating up to 40 bar
Wafer type connection (DIN/ANSI)
Rugged IP65 housing



IN-FLOW 'HIGH-FLOW' F-107CI

Min. flow 2 ... 100 m3n/h
Max. flow 20 ... 1000 m3n/h
Pressure rating up to 40 bar
Flanged connection (DIN/ANSI)
Rugged IP65 housing



BRONKHORST (UK) LTD

1 Kings Court

Willie Snaith Road

Newmarket Suffolk CB8 7TG

Tel. +44 1223 833222

sales@bronkhorst.co.uk

