

DATASHEET M15

mini CORI-FLOW™ M15

Low Flow Coriolis Mass Flow Meter / Controller



Low Flow Coriolis Mass Flow Meters / Controllers for Liquid and Gases

mini CORI-FLOW™ Mass Flow Meters and Controllers are precise and compact instruments, based on the [Coriolis measuring principle](#), designed to cover the needs of the low flow market. Bronkhorst® model M15 Mass Flow Meter (MFM) is suited for highly accurate measurement of gas or liquid flow in the range of 0...300 kg/h (which corresponds with 0...4000 l_n/min when used on nitrogen) at operating pressures up to 100 bar (higher on request). The instruments are equipped with a robust IP65 weatherproof housing and are optionally available with ATEX approval for use in Zone 2 hazardous areas.

The instrument contains a microprocessor based pc-board with signal and fieldbus conversion and a PID controller for optional mass flow control by means of a separately mounted control valve or pump.

Technical specifications

Measurement / control system

| | |
|--------------------------|---|
| Flow rates | Liquid: 0...300 kg/h (nominal flow rate: 100 kg/h); Gas: 0...4000 l _n /min (N ₂); Full Scale (FS) value is user-configurable |
| Mass flow accuracy | Liquid: ±0,2% Rd; Gas: ±0,5% Rd |
| Repeatability | ± 0,05 % of rate ± ½(ZS* x 100/actual flow)% |
| Turndown ratio | up to 1:100 |
| Zero stability (ZS) | < ± 50 g/h (Guaranteed at constant temperature and for unchanging process and environment conditions.) |
| Response time (sensor) | ≤ 200 msec |
| Temperature effect | on zero: < 5 g/h/°C; on span: < 0,001% Rd/°C; self heating (at zero flow): < 10°C (Depends on flow rate, heat capacity fluid, T amb., T fluid and cooling capacity.) |
| Operating temperature | 0 ... 70 °C; for ATEX Cat.3, Zone 2 max. 50°C |
| Mounting | any position, attitude sensitivity negligible. External shocks or vibrations should be avoided. |
| Temperature accuracy | ± 0,5 °C |
| Density accuracy | < ± 5 kg/m ³ (at full scale flow) |
| Leak integrity, outboard | tested < 2 x 10 ⁻⁹ mbar l/s He |
| Warm-up time | > 30 min for optimum accuracy |

Mechanical parts

| | |
|-------------------------|--|
| Sensor | single tube, DN 3.1 |
| Material (wetted parts) | stainless steel 316L / 1.4404; |
| Housing | stainless steel 430F |
| Pressure rating (PN) | 100 bar abs , higher on request |
| Process connections | compression type or face seal (VCR/VCO) couplings, or Tri-Clamp flanges (welded) |
| Seals | metal |
| Weight | 4,7 kg |
| Ingress protection | IP65 (weatherproof) |

Electrical properties

| | |
|------------------------|--|
| Power supply | +15...24 Vdc +/- 10% Max. ripple recommended: 50 mV tt |
| Max. power consumption | meter: max. 3 W; controller: max 7 W |
| Analog output | 0...5 (10) Vdc, min. load impedance > 2 k Ω ; 0 (4)...20 mA (sourcing), max. load impedance < 375 Ω |
| Analog setpoint | 0...5 (10) Vdc, min. load impedance > 100 k Ω 0 (4)...20 mA (sourcing), max. load impedance ~ 250 Ω |
| Digital communication | standard: RS232; options: PROFIBUS DP, DeviceNet™, Modbus RTU or FLOW-BUS |

Electrical connection

| | |
|---------------------------|--|
| Analog/RS232 | 8-pin DIN (male); |
| PROFIBUS DP | bus: 5-pin M12 (female); power: 8-pin DIN (male); |
| CANopen® / DeviceNet™ | 5-pin M12 (male); |
| FLOW-BUS/Modbus-RTU/ASCII | 5-pin M12 (male); |

Control valve options

External actuator options to be connected to the controller

Ex-proof specifications

Approvals / certificates

Technical specifications subject to change without notice.

For dimensional drawings and hook-up diagrams please visit the [product page](#) on our [website](#)

Recommended accessories



E-8000 SERIES DIGITAL READOUT / CONTROL SYSTEMS

Digital Readout / Control Systems

Bright, wide angle, 1.8" display (TFT technology)
User friendly operation, menu driven with 4 push buttons



BRIGHT SERIES COMPACT LOCAL R/C MODULE

Compact Local R/C Module

Bright, wide angle, 1.8" display
User friendly operation
Indication/operation/configuration



PIPS SERIES

Plug-in Power Supply

For lab-style or industrial devices
Interchangeable plugs (Euro, UK, USA, Australian, IEC) for mains connection

Related products



MINI CORI-FLOW™ M14

Flow range 0...30 kg/h
Pressure rating 200 bar
Independent of fluid properties
High accuracy, fast response



CORI-FLOW™ M54

Flow range 0...100 kg/h
Pressure rating 200 bar
Independent of fluid properties
High accuracy, fast response



CORI-FLOW™ M55

Flow range 0...600 kg/h
Pressure rating 100 bar
Independent of fluid properties
High accuracy, fast response



BRONKHORST (UK) LTD

1 Kings Court

Willie Snaith Road

Newmarket Suffolk CB8 7TG

Tel. [+44 1223 833222](tel:+441223833222)

sales@bronkhorst.co.uk

