

DATASHEET P-702CV

EL-PRESS P-702CV (P1-control)

Digital Electronic Back Pressure Controller



Digital Electronic Back Pressure Controllers

Bronkhorst® model P-702C Pressure Controllers (EPCs) are suited for precise measurement and control of upstream pressure ranges between 20...100 mbar and 12,8...64 bar absolute or between 7...35 mbar and 12,8...64 bar gauge. The EPC has a well-proven compact thru-flow design and includes a diaphragm type piezo-resistive pressure sensor, a microprocessor based pc-board with signal and fieldbus conversion and a compact, fast acting control valve.

EL-PRESS series are equipped with a digital pc-board, offering high accuracy, excellent temperature stability and fast response. The main digital pc-board contains all of the general functions needed for measurement and control. In addition to the standard RS232 output the instruments also offer analog I/O. As an option, an on-board interface can be mounted to provide CANopen®, DeviceNet™, EtherCAT®, PROFIBUS DP, PROFINET, Modbus RTU, ASCII or TCP/IP, EtherNet/IP, POWERLINK or FLOW-BUS protocols.

Technical specifications

Measurement / control system

Absolute pressure sensors	Code: 350A - Ranges (FS): 100 ... 350 mbara - P-max: 1,0 bara - Burst pressure: 1,4 bara Code: 1K1A - Ranges (FS): 0,35 ... 1,1 bara - P-max: 3,1 bara - Burst pressure: 4,2 bara Code: 6K0A - Ranges (FS): 1,1 ... 6 bara - P-max: 10,5 bara - Burst pressure: 14 bara Code: 21KA - Ranges (FS): 6 ... 21 bara - P-max: 62 bara - Burst pressure: 84 bara Code: M10A - Ranges (FS): 20 ... 100 bara - P-max: 200 bara - Burst pressure: n.a.
Relative pressure sensors	Code: 100R - Ranges (FS): 35 ... 100 mbarg - P-max: 0,7 barg - Burst pressure: 0,8 barg Code: 350R - Ranges (FS): 100 ... 350 mbarg - P-max: 1,0 barg - Burst pressure: 1,4 barg Code: 1k1R - Ranges (FS): 0,35 ... 1,1 barg - P-max: 3,1 barg - Burst pressure: 4,2 barg Code: 6K0R - Ranges (FS): 1,1 ... 6 barg - P-max: 10,5 barg - Burst pressure: 14 barg Code: 21KR - Ranges (FS): 6 ... 21 barg - P-max: 62 barg - Burst pressure: 84 barg
Accuracy (incl. linearity and hysteresis)	standard: $\pm 0,5$ % FS
Repeatability	< 0,1 % RD
Pressure rangeability	1 : 5 (with flow range 1 : 50)
Control stability	$\leq \pm 0,05$ % FS (typical for 1 l _n /min N ₂ at specified process volume)
Operating temperature	-10 ... +70 °C
Temperature sensitivity	0,1% FS/°C
Max. Kv-value	$6,6 \times 10^{-2}$
Leak integrity, outboard	tested < 2×10^{-9} mbar l/s He

Measurement / control system

Attitude sensitivity	max. error at 90° off horizontal < 0,3 mbar
Warm-up time	negligible

Mechanical parts

Material (wetted parts)	stainless steel 316L or comparable
Process connections	compression type or face seal (VCR/VCO) couplings
Seals	standard: Viton®; options: EPDM, Kalrez® (FFKM), FDA and USP Class VI approved compounds
Weight	0,7 kg
Ingress protection	IP40

Electrical properties

Power supply	+15 ... 24 Vdc			
Max. power consumption	Supply	at voltage I/O	at current I/O	extra for fieldbus
	15 V	290 mA	320 mA	<75 mA
	24 V	200 mA	215 mA	<50 mA
Analog output	0...5 (10) Vdc or 0 (4)...20 mA (sourcing output)			
Digital communication	standard: RS232; options: CANopen®, DeviceNet™, EtherCAT®, PROFIBUS DP, PROFINET, Modbus RTU, ASCII or TCP/IP, EtherNet/IP, POWERLINK or FLOW-BUS			

Electrical connection

Analog/RS232	9-pin D-connector (male);
PROFIBUS DP	bus: 9-pin D-connector (female); power: 9-pin D-connector (male);
CANopen® / DeviceNet™	5-pin M12-connector (male);
FLOW-BUS/Modbus-RTU/ASCII	RJ45 modular jack
Modbus TCP / EtherNet/IP / POWERLINK	2 x RJ45 modular jack (in/out);
EtherCAT®/ PROFINET	2 x RJ45 modular jack (in/out);

Control valve options

External actuator options to be connected to the controller

Ex-proof specifications

Approvals / certificates

Technical specifications subject to change without notice.

Note: The measuring cell of the pressure sensor is separated from the external pressure by a thin, sensitive stainless steel diaphragm, and the sealed off cavity between diaphragm and cell is filled with oil. Since the standard oil filling is flammable, Bronkhorst advises to take precautions when oxygen or any other explosive fluid is used.

For dimensional drawings and hook-up diagrams please visit the [product page](#) on our [website](#)

Recommended accessories



E-8000 SERIES

Digital Readout / Control Systems

Bright, wide angle, 1.8" display (TFT technology)

User friendly operation, menu driven with 4 push buttons



BRIGHT SERIES

Compact Local R/C Module

Bright, wide angle, 1.8" display

User friendly operation

Indication/operation/configuration



PIPS SERIES

Plug-in Power Supply

For lab-style or industrial devices

Interchangeable plugs (Euro, UK, USA, Australian, IEC) for mains connection

Related products



EL-PRESS P-712CV (P1-CONTROL)

Min. pressure 12,8...64 bar
Max. pressure 20...100 bar

Absolute or gauge pressure

High accuracy



EL-PRESS METAL SEALED P-702CM (P1-CONTROL)

Min. pressure 2...100 mbar
Max. pressure 1,28...64 bar

Metal-to-metal outer seals

Cleanroom assembled



IN-PRESS P-5X2CI+F-0XXAI (P1-CONTROL)

Min. pressure 2...100 mbar
Max. pressure 8...400 bar

Absolute or gauge pressure

Compact IP65 design



IQ+FLOW IQP-700C EPC (P1-CONTROL)

Min. pressure 0,1...0,5 bar
Max. pressure 2...10 bar

Ultra compact

MEMS technology



BRONKHORST (UK) LTD

1 Kings Court

Willie Snaith Road

Newmarket Suffolk CB8 7TG

Tel. +44 1223 833222

sales@bronkhorst.co.uk

