

# DATASHEET P-802CI

## IN-PRESS P-802CI

Process Pressure Controller, Industrial Style



### Process Pressure Controller, Industrial Style

Bronkhorst® model P-802CI Process Pressure Controllers (PPCs) are suited for precise pressure control with closed volumes, i.e. with one fluid connection. This PPC model is suited for pressure ranges between 17,5...350 mbar and 3,2...64 bar absolute or gauge. The instrument comprises a diaphragm type piezo-resistive pressure sensor, a microprocessor based pc-board with signal and fieldbus conversion and a PID controller for pressure control by means of two integrated control valves. This dual valve construction is a compact, economical alternative to configurations where forward pressure controllers are combined with separate bleed ports and relief valves. It is considered as a great advantage that the relief valve does not vent to the atmosphere. Furthermore the system can be set for either fast or smooth controlled (de)pressurization. The IN-PRESS model is of rugged design (IP65) for use in industrial environments.

IN-PRESS series are equipped with a digital pc-board, offering high accuracy, excellent temperature stability and fast response. The main digital pc-board contains all of the general functions needed for measurement and control. In addition to the standard RS232 output the instruments also offer analog I/O. As an option, an on-board interface can be mounted to provide CANopen®, DeviceNet™, EtherCAT®, PROFIBUS DP, PROFINET, Modbus RTU, ASCII or TCP/IP, EtherNet/IP, POWERLINK or FLOW-BUS protocols.

### Technical specifications

#### Measurement / control system

|   |   |
|---|---|
| Pressure ranges                           | min. 17,5 ... 350 mbar<br>max. 3,2 ... 64 bar |
| Accuracy (incl. linearity and hysteresis) | ± 0,5 % FS                                    |
| Repeatability                             | < 0,25 % RD                                   |
| Pressure rangeability                     | 1:20 (with flow range 1:50)                   |
| Response time (sensor)                    | 2 msec  |
| Operating temperature                     | -10 ... +70 °C                                |
| Temperature sensitivity                   | 0,1% FS/°C                                    |
| Leak integrity, outboard                  | tested < 2 x 10 <sup>-9</sup> mbar l/s He     |
| Attitude sensitivity                      | max. error at 90° off horizontal < 0,3 mbar   |
| Warm-up time                              | negligible                                    |

#### Mechanical parts

|                         |   |
|-------------------------|---|
| Material (wetted parts) | stainless steel 316L or comparable                |
| Process connections     | compression type or face seal (VCR/VCO) couplings |

## Mechanical parts

|                    |   |
|--------------------|---|
| Seals              | standard: FKM/Viton®;<br>options: EPDM, FFKM/Kalrez®, FDA and USP Class VI approved compounds |
| Weight             | 2,8 kg  |
| Ingress protection | IP65  |

## Electrical properties

|                        |  |                |                |                    |
|------------------------|--|----------------|----------------|--------------------|
| Power supply           | +15 ... 24 Vdc   |                |                |                    |
| Max. power consumption | Supply   | at voltage I/O | at current I/O | extra for fieldbus |
|                        | 15 V   | 290 mA         | 320 mA         | <75 mA             |
|                        | 24 V   | 200 mA         | 215 mA         | <50 mA             |
| PROFIBUS DP            | add 53 mA (15 V supply) or 30 mA (24 V supply)   |                |                |                    |
| CANopen® / DeviceNet™  | add 48 mA (24 V supply)  |                |                |                    |
| Analog output          | 0...5 (10) Vdc or 0 (4)...20 mA (sourcing output)  |                |                |                    |
| Digital communication  | standard: RS232;<br>options: CANopen®, DeviceNet™, EtherCAT®, PROFIBUS DP, PROFINET, Modbus RTU, ASCII or TCP/IP, EtherNet/IP, POWERLINK or FLOW-BUS |                |                |                    |

## Electrical connection

|   |   |
|---|---|
| Analog/RS232                            | 8 DIN (male);   |
| PROFIBUS DP                             | bus: 5-pin M12 (female);<br>power: 8 DIN (male);              |
| CANopen® / DeviceNet™                   | 5-pin M12-connector (male);                                   |
| FLOW-BUS/Modbus-RTU/ASCII               | 5-pin M12 (male)  |
| Modbus TCP / EtherNet/IP /<br>POWERLINK | bus: 2 x 5-pin M12 (female) (in/out);<br>power: 8 DIN (male); |
| EtherCAT®/ PROFINET                     | bus: 2 x 5-pin M12 (female) (in/out);<br>power: 8 DIN (male)  |

## Control valve options

## External actuator options to be connected to the controller

## Ex-proof specifications

## Approvals / certificates

Technical specifications subject to change without notice.

**Note:** The measuring cell of the pressure sensor is separated from the external pressure by a thin, sensitive stainless steel diaphragm, and the sealed off cavity between diaphragm and cell is filled with oil. Since the standard oil filling is flammable, Bronkhorst advises to take precautions when oxygen or any other explosive fluid is used.

For dimensional drawings and hook-up diagrams please visit the [product page](#) on our [website](#)

## Recommended accessories



### E-8000 SERIES

#### Digital Readout / Control Systems

Bright, wide angle, 1.8" display (TFT technology)  
User friendly operation, menu driven with 4 push buttons



### BRIGHT SERIES

#### Compact Local R/C Module

Bright, wide angle, 1.8" display  
User friendly operation  
Indication/operation/configuration



### PIPS SERIES

#### Plug-in Power Supply

For lab-style or industrial devices  
Interchangeable plugs (Euro, UK, USA, Australian, IEC) for mains connection

## Related products



### IN-PRESS P-812CI

Min. pressure 3,2...64 bar  
Max. pressure 5...100 bar  
Absolute or gauge pressure  
Fast or smooth pressure control  
Rugged IP65 construction



### IN-PRESS P-822CI

Min. pressure 5...100 bar  
Max. pressure 10...200 bar  
Absolute or gauge pressure  
Fast or smooth pressure control  
Rugged IP65 construction



### EL-PRESS P-802CV

Min. pressure 17,5...350 mbar  
Max. pressure 3,2...64 bar  
Absolute or gauge pressure  
Fast or smooth pressure control

