

DATASHEET F-001

Series F-001, F-011, F-021

Direct-operated control valves



Low Flow Control Valves for Gases

Control valves F-001 / F-011 are suitable for low flow rates (up to approx. 50 l_n/min N₂-equivalent) with pressure ratings up to 64 resp. 100 bar. The F-001 valve module is also used as pilot valve in bigger valves and controllers. F-021 is a direct acting control valve for high pressure applications, up to 200 bar.

Technical specifications

Measurement / control system

Operating temperature
F-001AV / F-011AV / F-021AV: -10...+70°C
F-001AI / F-011AI / F-021AI: -10...+70°C
F-001AX / F-011AX: -10...+65°C

Max. Kv-value
F-001 series: $6,6 \times 10^{-2}$
F-011 series: $6,6 \times 10^{-2}$
F-021 series: $1,56 \times 10^{-3}$

Leak integrity, outboard
tested $< 2 \times 10^{-9}$ mbar l/s He

Mechanical parts

Material (wetted parts)
stainless steel 316L/320;
other on request

Pressure rating (PN)
F-001 series: 64 bar(a)
F-011 series: 100 bar(a)
F-021 series: 200 bar(a)

Max. ΔP
contact distributor (depends on Kv-value)

Process connections
compression type or face seal (VCR/VCO) couplings

Seals
< 100 bar: standard: Viton®;
options: EPDM, Kalrez® (FFKM), FDA and USP Class VI approved compounds
> 100 bar: Viton

Protection class
F-001AV / F-011AV / F-021AV: IP40
F-001AI / F-011AI / F-021AI: IP65
F-001AX-XBB / F-011AX-XBB: II 1 G/D Ex ia IIC T6
F-001AX-XCB / F-011AX-XCB: II 2 G/D Ex e mb T4

Plunger
< 100 bar: standard: Viton®;
options: EPDM, Kalrez® (FFKM), FDA and USP Class VI approved compounds
> 100 bar: Viton

Electrical properties

Supply voltage	IP40 / IP65 style: 15 Vdc or 24 Vdc; Ex-proof coil XBB: max. 28 Vdc/110 mA; Ex-proof coil XCB: max. 24 Vdc
Valve control signal	0... 185 mA
Coil resistance	IP40 / IP65 style: 62 Ohm; Ex-proof coil XBB: 295 Ohm; Ex-proof coil XCB: 65 Ohm (at 20°C)
De-energized position	Standard: Normally closed; Option: Normally opened
Electrical connection	IP40 coil: shielded cable; IP65 coil: DIN 43650 connection; Ex-proof coils: cable gland M20x1,5

Electrical connection

Control valve options

External actuator options to be connected to the controller

Ex-proof specifications

Approvals / certificates

Technical specifications subject to change without notice.

For dimensional drawings and hook-up diagrams please visit the [product page](#) on our [website](#)

Related products



SERIES F-033, F-042

Vary-P Control Valves

Flow up to approx. 100

l/min

Pressure up to 400/700 bar

For high (differential)
pressures applications



SERIE F-002A, F-003A, F-003B

Pilot-Operated Control Valves

Flow up to approx. 500

m³/h

Pressure up to 64/100 bar

Kv: 0.04...6.0



SERIES F-004A, F-004B

Bellows Valves with Pressure Compensation

Flow up to approx. 1000

l/min

For low (differential)
pressure applications

Kv: 0.03...1.0



BRONKHORST USA LLC

57 South Commerce Way

Suite 120

USA - Bethlehem, PA 18017

Tel. [+1-610-866-6750](tel:+1-610-866-6750)

sales@bronkhorstusa.com

