

F-221MI

IN-FLOW F-221MI

Industrial Style High-Pressure Mass Flow Controller for Gases

- High accuracy, excellent repeatability
- Fast response
- Operating pressure / delta-P up to 200 bar
- Compact, rugged design (IP65, dust and waterproof)
- Virtually pressure and temperature independent



Industrial Style Gas Mass Flow Controllers for High Pressure / High Delta-P

Bronkhorst® model F-221MI Mass Flow Controllers (MFCs) are suited for accurate measurement and control of flow ranges between 0,3...15 ml_n/min and 0,4...20 l_n/min with an operating pressure up to 200 bar and max. 200 bar pressure difference (ΔP). The MFC consists of a thermal mass flow sensor, a precise control valve and a microprocessor based pc-board with signal and fieldbus conversion. As a function of a setpoint value, the flow controller swiftly adjusts the desired flow rate. The IN-FLOW model is of rugged design (IP65) for use in industrial environments or even Zone 2 hazardous areas, with optional ATEX Cat. 3 or FM Class I, Div. 2 approval.

IN-FLOW series are equipped with a digital pc-board, offering high accuracy, excellent temperature stability and fast response. The main digital pc-board contains all of the general functions needed for measurement and control. In addition to the standard RS232 output the instruments also offer analog I/O. As an option, an on-board interface can be mounted to provide CANopen®, DeviceNet™, PROFIBUS DP, PROFINET, Modbus RTU/ASCII or FLOW-BUS protocols.

Technical specifications

Measurement / control system

Flow range (intermediate ranges available)	min. 0,3...15 ml _n /min max. 0,4...20 l _n /min (based on N ₂)			
Accuracy (incl. linearity) (based on actual calibration)	±0,5% Rd plus ±0,1% FS			
Repeatability	< 0,2 % RD			
Turndown ratio	1:50			
Multi fluid capability	storage of max. 8 calibration curves			
Settling time (in control, typical)	2 ... 4 sec.			
Control stability	< ± 0,1 % FS			
Operating temperature	-10 ... +70 °C for ATEX cat. 3 and FM Class 1 Div 2 : 0...50°C			
Temperature sensitivity	zero: < 0,05% FS/°C; span: < 0,05% Rd/°C			
Pressure sensitivity	0,1% Rd/bar typical N ₂ ; 0,01% Rd/bar typical H ₂			
Max. Kv-value	1,5 x 10 ⁻³			
Leak integrity, outboard	tested < 2 x 10 ⁻⁹ mbar l/s He			
Attitude sensitivity	max. error at 90° off horizontal 0,2% at 1 bar, typical N ₂			
Warm-up time	30 min. for optimum accuracy 2 min for accuracy ± 2% FS			

Mechanical parts

Material (wetted parts)	stainless steel 316L or comparable			
Pressure rating (PN)	200 bar abs			
Process connections	compression type or face seal coupling			
Seals	Viton®			
Ingress protection	IP65			

Electrical properties

Power supply	+15 ... 24 Vdc			
Max. power consumption	Supply	at voltage I/O	at current I/O	extra for fieldbus
	15 V	290 mA	320 mA	<75 mA
	24 V	200 mA	215 mA	<50 mA
Analog output	0...5 (10) Vdc or 0 (4)...20 mA (sourcing output)			
Digital communication	standard: RS232; options: CANopen®, DeviceNet™, PROFIBUS DP, PROFINET, Modbus RTU/ASCII or FLOW-BUS			

Electrical connection

Analog/RS232	8 DIN (male);
PROFIBUS DP	bus: 5-pin M12 (female); power: 8 DIN (male);
CANopen® / DeviceNet™	5-pin M12 (male);
FLOW-BUS/Modbus-RTU/ASCII	5-pin M12 (male)
PROFINET	bus: 2 x 5-pin M12 (female) (in/out); power: 8 DIN (male);
IEC 61010-1	IEC-61010-1:2010 including national deviations for UL (61010-1:2012) and CSA (C22.2 No. 61010-1-12)

Technical specifications subject to change without notice.

For dimensional drawings and hook-up diagrams please visit the [product page](#) on our [website](#)

Recommended accessories



E-8000 SERIES

Digital Readout / Control Systems

Bright, wide angle, 1.8" display (TFT technology)
User friendly operation, menu driven with 4 push buttons



BRIGHT SERIES

Compact Local R/C Module

Bright, wide angle, 1.8" display
User friendly operation
Indication/operation/configuration



PIPS SERIES

Plug-in Power Supply

For lab-style or industrial devices
Interchangeable plugs (Euro, UK, USA, Australian, IEC) for mains connection



IN-LINE FILTER SERIE M-411 RS

1/4" female in / male out
100 bar
Average porosity 0.5...15 μm

Related products



IN-FLOW F-122MI

Min. flow 0,3 ... 15 l/min
Max. flow 5 ... 250 l/min
Pressure rating 200 bar
Compact IP65 design
High accuracy



IN-FLOW F-231MI

Min. flow 0,01 ... 0,5 l/min
Max. flow 0,2 ... 10 l/min
Pressure / ΔP up to 400 bar
Compact design
High accuracy and repeatability



IN-FLOW F-232MI

Min. flow 0,2 ... 10 l/min
Max. flow 2 ... 100 l/min
Pressure / ΔP up to 400 bar
Compact IP65 design
High accuracy and repeatability



BRONKHORST USA INC.

57 South Commerce Way

Suite 120

USA - Bethlehem, PA 18017

Tel. [+1-610-866-6750](tel:+1-610-866-6750)

sales@bronkhorstusa.com