

DATASHEET F-106XD

LOW- Δ P-FLOW F-106xD

Mass Flow Meter for low pressure drop or corrosive gas service, industrial style



Thermal Mass Flow Meters for low pressure drop or corrosive gas applications, industrial style

Bronkhorst® model F-106xD* Mass Flow Meters (MFMs) are suited for precise measurement of flow ranges between 0,2...10 m³_n/h and 20...1000 m³_n/h (N₂-equivalent). The instruments are particularly suited for corrosive gases or applications with very low differential pressure (Δ P). Compared to conventional instruments, LOW- Δ P-FLOW meters have larger flow channels to minimize the risk of clogging, facilitate cleaning and purging, and cause lower pressure drop (the sensor only requires 0,5 to 5 mbar). This model is of rugged design (IP65) for use in industrial environments or even Zone 2 hazardous areas, with optional ATEX Cat. 3 or FM Class I, Div. 2 approval.

The integrated digital pc-board provides signal and fieldbus conversion as well as PID controller functionality for optional mass flow control by means of a (separately mounted) control valve. In addition to the standard RS232 output the instruments also offer analog I/O. As an option, an on-board interface can be mounted to provide CANopen®, DeviceNet™, EtherCAT®, PROFIBUS DP, PROFINET, Modbus RTU, ASCII or TCP/IP, EtherNet/IP, POWERLINK or FLOW-BUS protocols.

* Series F-106xD consists of the models F-106AD (DIN DN 40 / ANSI 1½"), F-106BD (DIN DN 50 / ANSI 2"), F-106CD (DIN DN 80 / ANSI 3") and F-106DD (DIN DN 100 / ANSI 4")

Technical specifications

Measurement / control system

| | |
|--|---|
| Flow range (intermediate ranges available) | min. 0,2...10 m ³ _n /h max. 20...1000 m ³ _n /h (based on N ₂) |
| Accuracy (incl. linearity) (based on actual calibration) | ± 1 % FS |
| Repeatability | < 0,2 % RD |
| Turndown ratio | 1:50 (2...100%) |
| Max. operating pressure | 10 bar g |
| Multi fluid capability | Storage of max. 8 calibration curves |
| Response time (sensor) | 1 ... 2 sec. |
| Operating temperature | -10 ... +70 °C for ATEX cat. 3 and FM Class 1 Div 2 : 0...50°C |
| Mounting | horizontal |
| Temperature sensitivity | < 0,1% FS/°C |
| Pressure sensitivity | 0,1% Rd/bar typical N ₂ |
| Leak integrity, outboard | tested < 2 x 10 ⁻⁹ mbar l/s He |

Measurement / control system

| | |
|--------------|---|
| Warm-up time | 30 min. for optimum accuracy 2 min for accuracy $\pm 2\%$ FS |
|--------------|---|

Mechanical parts

| | |
|-------------------------|---|
| Material (wetted parts) | stainless steel 316L or comparable; other on request |
| Process connections | wafer type, for mounting between flanges |
| Seals | standard: FKM/Viton®; options: EPDM, FFKM/Kalrez® |
| Ingress protection | IP65 |

Electrical properties

| | | | | |
|-----------------------------------|--|----------------|----------------|--------------------|
| Power supply | +15 ... 24 Vdc | | | |
| Max. power consumption meter | Supply | at voltage I/O | at current I/O | extra for fieldbus |
| | 15 V | 95 mA | 125 mA | <75 mA |
| | 24 V | 65 mA | 85 mA | <50 mA |
| Max. Power consumption controller | Supply | at voltage I/O | at current I/O | extra for fieldbus |
| | 15 V | 290 mA | 320 mA | <75 mA |
| | 24 V | 200 mA | 215 mA | <50 mA |
| Analog output | 0...5 (10) Vdc or 0 (4)...20 mA (sourcing output) | | | |
| Digital communication | standard: RS232; options: CANopen®, DeviceNet™, EtherCAT®, PROFIBUS DP, PROFINET, Modbus RTU, ASCII or TCP/IP, EtherNet/IP, POWERLINK or FLOW-BUS | | | |

Electrical connection

| | |
|---|---|
| Analog/RS232 | 8 DIN (male); |
| PROFIBUS DP | bus: 5-pin M12 (female); power: 8 DIN (male); |
| CANopen® / DeviceNet™ | 5-pin M12 (male); |
| FLOW-BUS/Modbus-RTU/ASCII | 5-pin M12 (male) |
| Modbus TCP / EtherNet/IP / POWERLINK | bus: 2 x 5-pin M12 (female) (in/out); power: 8 DIN (male); |
| EtherCAT®/ PROFINET | bus: 2 x 5-pin M12 (female) (in/out); power: 8 DIN (male) |
| IEC 61010-1 | IEC-61010-1:2010 including national deviations for UL (61010-1:2012) and CSA (C22.2 No. 61010-1-12) |

Control valve options

External actuator options to be connected to the controller

Ex-proof specifications

Approvals / certificates

Technical specifications subject to change without notice.

For dimensional drawings and hook-up diagrams please visit the [product page](#) on our [website](#)

Recommended accessories



E-8000 SERIES

Digital Readout / Control Systems

Bright, wide angle, 1.8" display (TFT technology)
User friendly operation, menu driven with 4 push buttons



BRIGHT SERIES

Compact Local R/C Module

Bright, wide angle, 1.8" display
User friendly operation
Indication/operation/configuration



PIPS SERIES

Plug-in Power Supply

For lab-style or industrial devices
Interchangeable plugs (Euro, UK, USA, Australian, IEC) for mains connection

Related products



LOW-ΔP-FLOW F-103EI

Min. flow 0,9...45 l/min
Max. flow 4...200 l/min
Pressure rating up to 10 bar
Low ΔP, easy to purge
Compact IP65 design



LOW-ΔP-FLOW F-107XD

Min. flow 0,2...10 m³/h
Max. flow 20...1000 m³/h
Pressure rating up to 10 bar
Low ΔP, easy to purge
IP65, flanged type

