

F-202DV

LOW- Δ P-FLOW F-202DV

Mass Flow Controller for low pressure drop or corrosive gas service

- Large bore capillary (thermal bypass sensor)
- Very low pressure drop
- Less sensitivity to humidity or dirt
- Suitable of corrosive gases
- Easy to purge



Thermal Mass Flow Controllers for low pressure drop or corrosive gas applications

Bronkhorst® model F-202DV Mass Flow Controllers (MFCs) are suited for precise measurement of flow ranges between 0,28...14 l_n/min and 0,5...25 l_n/min (N₂-equivalent). The instruments are particularly suited for corrosive gases or applications with very low differential pressure (Δ P). Compared to conventional instruments, LOW- Δ P-FLOW MFCs have larger flow channels to minimize the risk of clogging, facilitate cleaning and purging, and cause lower pressure drop (the sensor only requires 0,5 to 5 mbar).

The integrated digital pc-board provides signal and fieldbus conversion as well as PID controller functionality for mass flow control by means of the integrated control valve. In addition to the standard RS232 output the instruments also offer analog I/O. As an option, an on-board interface can be mounted to provide CANopen®, DeviceNet™, EtherCAT®, PROFIBUS DP, PROFINET, Modbus RTU, ASCII or TCP/IP, EtherNet/IP or FLOW-BUS protocols.

Technical specifications

Measurement / control system

Flow range (intermediate ranges available) min. 0,28...14 I_n/min
max. 0,5...25 I_n/min
(based on N₂)

Accuracy (incl. linearity) (based on actual calibration) ± 1 % FS

Repeatability < 0,2 % RD

Turndown ratio 1:50 (2...100%)

Max. operating pressure 10 bar g

Multi fluid capability storage of max. 8 calibration curves

Settling time (in control, typical) 2 ... 3 sec.

Control stability < ± 0,1 % FS (typical)

Operating temperature -10 ... +70

Mounting horizontal

Temperature sensitivity < 0,1% FS/°C

Pressure sensitivity 0,1% Rd/bar typical N₂

Max. Kv-value $6,6 \times 10^{-2}$

Leak integrity, outboard tested < 2×10^{-9} mbar l/s He

Warm-up time 30 min. for optimum accuracy
2 min for accuracy ± 2% FS

Mechanical parts

Material (wetted parts) stainless steel 316L or comparable;
other on request

Process connections compression type or face seal (VCR/VCO) couplings

Seals standard: Viton®;
options: EPDM, Kalrez® (FFKM), FDA and USP Class VI approved compounds

Weight 0,8 kg

Ingress protection IP40

Electrical properties

Power supply +15 ... 24 Vdc

Max. power consumption	Supply	at voltage I/O	at current I/O	extra for fieldbus
	15 V	290 mA	320 mA	<75 mA
	24 V	200 mA	215 mA	<50 mA

Analog output 0...5 (10) Vdc or 0 (4)...20 mA (sourcing output)

Digital communication standard: RS232;
options: PROFIBUS DP, CANopen®, DeviceNet™, PROFINET, EtherCAT®, Modbus RTU, ASCII or TCP/IP, EtherNet/IP, FLOW-BUS

Electrical connection

Analog/RS232	9-pin D-connector (male);
PROFIBUS DP	bus: 9-pin D-connector (female); power: 9-pin D-connector (male);
CANopen® / DeviceNet™	5-pin M12-connector (male);
FLOW-BUS/Modbus-RTU/ASCII	RJ45 modular jack
Modbus TCP / EtherNet/IP	2 x RJ45 modular jack (in/out);
EtherCAT®/ PROFINET	2 x RJ45 modular jack (in/out);

Technical specifications subject to change without notice.

For dimensional drawings and hook-up diagrams please visit the [product page](#) on our [website](#)

Recommended accessories



E-8000 SERIES

Digital Readout / Control Systems

Bright, wide angle, 1.8" display (TFT technology)

User friendly operation, menu driven with 4 push buttons



BRIGHT SERIES

Compact Local R/C Module

Bright, wide angle, 1.8" display

User friendly operation

Indication/operation/configuration



PIPS SERIES

Plug-in Power Supply

For lab-style or industrial devices

Interchangeable plugs (Euro, UK, USA, Australian, IEC) for mains connection



IN-LINE FILTER SERIE M-422 RS

1/4" female in / male out

200 bar

Average porosity 2...20 µm

Related products



LOW-ΔP-FLOW F-201EV

Min. flow 0,028...1,4 l/min
Max. flow 0,24...12 l/min
Pressure rating up to 10 bar
Low ΔP, easy to purge
Compact design



LOW-ΔP-FLOW F-202EV

Min. flow 0,17...8,5 l/min
Max. flow 1...50 l/min
Pressure rating up to 10 bar
Low ΔP, easy to purge
Compact design



LOW-ΔP-FLOW F-202DI

Min. flow 0,28...14 l/min
Max. flow 0,5...25 l/min
Pressure rating up to 10 bar
Low ΔP, easy to purge
Compact IP65 design



LOW-ΔP-FLOW F-102D

Min. flow 0,28...14 l/min
Max. flow 0,5...25 l/min
Pressure rating up to 10 bar
Very low pressure drop
Suitable for corrosive gases



BRONKHORST USA INC.

57 South Commerce Way

Suite 120

USA - Bethlehem, PA 18017

Tel. +1-610-866-6750

sales@bronkhorstusa.com