DATASHEET MV-394-H2

MASS-VIEW® MV-394-H2

Hydrogen Flow Regulator with integrated display

MASSFLOW-ONLINE PRODUCT



Hydrogen Mass Flow Regulators with integrated display

MASS-VIEW® model MV-394-H2 Mass Flow Regulators (MFRs) are suited for precise measurement and control of flow ranges between 0,1…1 l_n/min and 0.1…10 l_n/min hydrogen at operating pressures up to 10 bar(g). The MFR has an integrated graphical OLED display, clearly visible at wide angles, which allows reading of actual flow (value and a bar graph), total flow and type of gas. A high quality needle valve offers smooth and fine adjustment of the gas flow.

The display features easy set up via a user-friendly menu, using a 4-way navigation push button. Features & functions include a variety of alarm and counter functions, an analog output signal, digital interfaces and two relay contacts.

The MASS-VIEW® series provides modern, novel and economical alternative to variable area meters (VA meters), also known as purge meters. Unlike conventional VA meters these new flow meters measure mass flow instead of volume flow.

Technical specifications

Measurement / control system

Flow range (intermediate ranges available)	min. 0,1…1 l_n/min max. 0.1…10 l_n/min (based on H_2)
Accuracy (incl. linearity) (based on actual calibration)	± 2% Rd for flow > 50% of max. capacity; ± (1% Rd + 0,5% FS) on lower flows
Repeatability	< 0,2 % FS typical
Turndown ratio	up to 1 : 100
Operating pressure	0 … 10 bar(g) / 0 … 150 psi(g)
Pressure coefficient	± 0,2% Rd/bar typical at Air
Standard calibration gas	H_2
Response time (sensor)	2 sec.
Operating temperature	0 … 50 °C (32 … 122°F)
Temperature coefficient	Zero: <0,1% FS/°C, Span: <0,2% Rd/°C
Leak integrity, outboard	tested < 2 x 10^{-9} mbar l/s He
Attitude sensitivity	< 0,1 % FS

Mechanical parts

Material (wetted parts)	Meter: Aluminium; Needle valve: SS316
Test pressure	21 bar(a) / 300 psi(a)
Process connections	G 1/4" BSPP female thread (compression fittings optional)
Seals	Viton®, PTFE
Weight	0,7 kg
Ingress protection	IP40

Electrical properties

Power supply	+15 … 24 Vdc (+/- 10%)
Max. power consumption	approx. 135 mA
Analog output	0 … 5 Vdc
Digital communication	RS232 / RS485 (Modbus RTU/ASCII)
Min. and max. relay contacts	switching current 0,5 A, 24 Vdc, one side grounded (0 Vdc power)
Electrical connection	8-pin RJ-45 modular jack

Electrical connection

Control valve options

External actuator options to be connected to the controller

Ex-proof specifications

Approvals / certificates

Technical specifications subject to change without notice.

For dimensional drawings and hook-up diagrams please visit the product page on our website

Related products



MASS-VIEW® MV-304

Min. flow 0,04...2 ln/min
Max. flow 0,2...20 ln/min

Pressure rating 10 bar

Bright, graphical OLED display

High quality needle valve



MASS-VIEW® MV-392-H2

Min. flow 50...100 mln/min H2
Max. flow 50...1000 mln/min H2

Bright, graphical OLED display

High quality needle valve



MASS-VIEW® MV-396-H2

Min. flow 0,2...10 ln/min H2
Max. flow 1...100 ln/min H2

Bright, graphical OLED display

High quality needle valve

Bronkhorst®

www.bronkhorst.com

Bronkhorst High-Tech designs and manufactures innovative instruments and subsystems for low-flow measurement and control for use in laboratories, machinery and industry. Driven by a strong sense of sustainability and with many years of experience, we offer an extensive range of (mass) flow meters and controllers for gases and liquids, based on thermal, Coriolis and ultrasonic measuring principles. Our global sales and service network provides local support in more than 40 countries. Discover Bronkhorst®!