

F-231MX

EX-FLOW F-231MX

High-Pressure Mass Flow Controller for Gases, Ex-Protected style

- ATEX approval Cat.2, Zone 1
- High accuracy, excellent repeatability
- Virtually pressure and temperature independent
- Operating pressure / delta-P up to 400 bar



Intrinsically Safe Gas Mass Flow Controllers for High Pressure / High Delta-P

Bronkhorst® EX-FLOW Mass Flow Controllers (MFCs) are suited for precise gas flow control in ATEX Zone 1 hazardous areas. The flow meter part and the control valve of the MFC should be connected (via separate cables) to a power supply with galvanic isolation / preamplifier / readout system (located in the safe zone) which contains a controller board to complete the control loop. See Bronkhorst® [E-8000 Series](#).

EX-FLOW model F-231MX covers flow ranges from 10...500 ml_n/min up to 0,2...10 l_n/min (N₂-equivalent) at operating pressures up to 400 bar and max. 400 bar pressure difference (ΔP).

The intrinsically safe measuring head of the flow meter is tested according to ATEX 114 Directive 2014/34/EU and approved under EC-Type Examination Number: KEMA 01ATEX1172, protection II 2 G Ex ib IIC T4 Gb.

The intrinsically safe valve coils are explosion proof certified and available in two options (ATEX certification only):

Coil XB: protection II 1 G Ex ia IIC T6 / protection II 1 D Ex ta IIIC T80°C

Coil XC: protection II 2 G Ex eb IIC T4 / protection II 2 D Ex tb IIIC T130°C

Technical specifications

Measurement / control system

Flow range (intermediate ranges available) min. 10...500 ml_n/min
max. 0,2...10 l_n/min
(based on N₂)

Accuracy (incl. linearity) (based on actual calibration) ± 1 % FS

Repeatability < 0,2 % RD

Turndown ratio 1:50 (2...100%)

Time constant 5 sec.

Control stability ≤ ± 0,1 % FS typical

Operating temperature -10 ... +65 °C

Temperature sensitivity zero: < 0,05% FS/°C; span: < 0,05% Rd/°C

Leak integrity, outboard tested < 2 x 10⁻⁹ mbar l/s He

Attitude sensitivity max. error at 90° off horizontal 0,2% FS at 1 bar, typical N₂

Warm-up time 30 min. for optimum accuracy
2 min. for accuracy ± 2% FS

Mechanical parts

Material (wetted parts)	Stainless steel 316L or comparable
Pressure rating (PN)	400 bar abs
Min. ΔP	6 bar dif.
Max. ΔP	up to 400 bar dif.
Process connections	compression type or face seal (VCR/VCO) couplings
Seals	standard: Viton®; options: EPDM, Kalrez® (FFKM)
Ingress protection	IP65

Electrical properties

Output signal	15 ... 20 mA (linear) Terminal connection, cable gland M16x1,5
I/O signals via PS/Readout (located in safe area)	analog: 0...5 Vdc, 0...10 Vdc, 0...20 mA, 4...20 mA; digital: RS232, PROFIBUS DP, DeviceNet™, Modbus RTU or ASCII, PROFINET, EtherCAT®, FLOW-BUS
XB-coil	Coil voltage max. 28 V/110 mA; 295 Ohm at 20°C
XC-coil	Coil voltage max. 24 V; 65 Ohm at 20°C, Pmax = 9 W at 20°C

Electrical connection

Ex-proof measuring head	Terminal connection, cable gland M16x1,5
Control valve coil	cable gland M20x1,5

Control valve options


External actuator options to be connected to the controller

Ex-proof specifications

Approvals / certificates

Technical specifications subject to change without notice.

For dimensional drawings and hook-up diagrams please visit the [product page](#) on our [website](#)




Recommended accessories



E-8000 SERIES

Digital Readout / Control Systems

- Bright, wide angle, 1.8" display (TFT technology)
- User friendly operation, menu driven with 4 push buttons



Related products



EX-FLOW F-131MX

Flow ranges from 0,3...15 mln/min up to
0,4...20 lln/min
Pressure rating 400 bar
ATEX approval Cat.2, Zone 1
Rugged IP65 construction



EX-FLOW F-230MX

Min. flow 0,2...10 mln/min
Max. flow 10...500 mln/min
Pressure / ΔP up to 400 bar
ATEX approval Cat.2, Zone 1
Rugged IP65 construction



EX-FLOW F-232MX

Min. flow 0,2...10 lln/min
Max. flow 2...100 lln/min
Pressure / ΔP up to 400 bar
ATEX approval Cat.2, Zone 1
Rugged IP65 construction



BRONKHORST HIGH-TECH B.V.

Nijverheidsstraat 1A
NL-7261 AK Ruurlo (NL)
Tel. [+31 573 45 88 00](tel:+31573458800)
info@bronkhorst.com

