

F-201AI

IN-FLOW F-201AI

Industrial Style Thermal Mass Flow Controller for Gases

- High accuracy
- Fast response, excellent repeatability
- Optional Multi Fluid / Multi Range functionality
- Virtually pressure and temperature independent
- Compact, rugged design (IP65, dust and waterproof)



Industrial Style Gas Mass Flow Controllers for low/medium flow rates

Bronkhorst® model F-201AI Mass Flow Controllers (MFCs) are suited for accurate measurement and control of flow ranges between 0,4...20 I_n /min and 2...100 I_n /min with pressure rating between vacuum and 64 bar. The MFC consists of a thermal mass flow sensor, a precise control valve and a microprocessor based pc-board with signal and fieldbus conversion. As a function of a setpoint value, the flow controller swiftly adjusts the desired flow rate. The IN-FLOW model is of rugged design (IP65) for use in industrial environments or even Zone 2 hazardous areas, with optional ATEX Cat. 3 or FM Class I, Div. 2 approval.

IN-FLOW series are equipped with a digital pc-board, offering high accuracy, excellent temperature stability and fast response. The main digital pc-board contains all of the general functions needed for measurement and control. In addition to the standard RS232 output the instruments also offer analog I/O. As an option, an on-board interface can be mounted to provide DeviceNet™, PROFIBUS DP, PROFINET, Modbus, or FLOW-BUS protocols. The IN-FLOW model features optional Multi Gas / Multi Range functionality, providing (OEM-) customers with optimal flexibility and process efficiency.

Technical specifications

Measurement / control system

Flow range, based on N ₂ (intermediate ranges available)	min. 0,4...20 I _N /min max. 2...100 I _N /min
Accuracy (incl. linearity) (based on actual calibration)	±0,5% Rd plus ±0,1% FS
Turndown	1:50 (in digital mode up to 1:187,5)
Multiple fluid capability	storage of max. 8 calibration curves optional Multi Gas / Multi Range functionality up to 10 bar abs
Repeatability	< 0,2% Rd
Settling time (controller)	standard: 1...2 seconds option: down to 500 msec
Control stability	< ±0,1% FS
Max. Kv-value	6,6 x 10 ⁻²
Operating temperature	-10...+70°C; for ATEX cat. 3 and FM Class 1 Div 2 : 0...50°C
Temperature sensitivity	zero: < 0,05% FS/°C; span: < 0,05% Rd/°C
Pressure sensitivity	0,1% Rd/bar typical N ₂ ; 0,01% Rd/bar typical H ₂
Leak integrity, outboard	tested < 2 x 10 ⁻⁹ mbar l/s He
Attitude sensitivity	max. error at 90° off horizontal 0,2% at 1 bar, typical N ₂
Warm-up time	30 min. for optimum accuracy 2 min for accuracy ± 2% FS

Mechanical parts

Material (wetted parts)	stainless steel 316L or comparable
Pressure rating	64 bar abs
Process connections	compression type or face seal couplings
Seals	standard: Viton [®] ; options: EPDM, Kalrez [®] (FFKM)
Weight	1,5 kg
Ingress protection (housing)	IP65

Electrical properties

Power supply	+15...24 Vdc									
Max. power consumption	<table><thead><tr><th>Supply</th><th>at voltage I/O</th><th>at current I/O</th></tr></thead><tbody><tr><td>15 V</td><td>290 mA</td><td>320 mA</td></tr><tr><td>24 V</td><td>200 mA</td><td>215 mA</td></tr></tbody></table>	Supply	at voltage I/O	at current I/O	15 V	290 mA	320 mA	24 V	200 mA	215 mA
Supply	at voltage I/O	at current I/O								
15 V	290 mA	320 mA								
24 V	200 mA	215 mA								
PROFIBUS DP	add 53 mA (15 V supply) or 30 mA (24 V supply)									
PROFINET	add 77 mA (15 V supply) or 48 mA (24 V supply)									
DeviceNet™	add 48 mA (24 V supply)									
Analog output/command	0...5 (10) Vdc or 0 (4)...20 mA (sourcing output)									
Digital communication	standard: RS232; options: PROFIBUS DP, PROFINET, DeviceNet™, Modbus RTU or ASCII, FLOW-BUS									

Electrical connection

Analog/RS232	8 DIN (male);
PROFIBUS DP	bus: 5-pin M12 (female); power: 8 DIN (male);
PROFINET	bus: 2 x 5-pin M12 (female) (in/out); power: 8 DIN (male);
Devicenet™	5-pin M12 (male);
FLOW-BUS/Modbus-RTU/ASCII	5-pin M12 (male)

Technical specifications and dimensions subject to change without notice.

For dimensional drawings and hook-up diagrams please visit the [productpage](#) on our [website](#)

Recommended accessories



E-8000 - DIGITAL READOUT / CONTROL SYSTEMS

Bright, wide angle, 1.8" display (TFT technology)

User friendly operation, menu driven with 4 push buttons



BRIGHT - COMPACT LOCAL READOUT/CONTROL MODULE

Bright, wide angle, 1.8" display

User friendly operation

Indication/operation/configuration



PIPS - PLUG-IN POWER SUPPLY

For lab-style or industrial devices

Interchangeable plugs (Euro, UK, USA, Australian, IEC) for mains connection



IN-LINE FILTER SERIES M-411 RS

1/4" female in / male out

100 bar

Average porosity 0.5...15 μm

Related products



IN-FLOW F-201CI

Min. flow 0,16...8 mln/min
Max. flow 0,5...25 ln/min
Pressure rating 64 bar
Compact IP65 design
High accuracy and repeatability



IN-FLOW F-202AI

Min. flow 0,8...40 ln/min
Max. flow 5...250 ln/min
Pressure rating 64 bar
Compact IP65 design
High accuracy and repeatability



IN-FLOW F-111AI

Min. flow 0,4...20 ln/min
Max. flow 0,6...100 ln/min
Pressure rating 100 bar
Compact IP65 design
High accuracy



BRONKHORST HIGH-TECH B.V.

Nijverheidsstraat 1A
NL-7261 AK Ruurlo (NL)
Tel. [+31 573 45 88 00](tel:+31573458800)
info@bronkhorst.com