

μ-FLOW L01

Ultra Low-Flow Thermal Liquid Mass Flow Meter

- Fast and accurate measuring signal
- Insensitive to mounting position
- Very small internal volume (sensor: 1,5...33 μl)
- Suitable for liquids with low boiling points
- Analog, RS232 or fieldbus communication



Liquid Mass Flow Meters for Ultra Low Flow Rates

Bronkhorst® model L01 Liquid Flow Meters (LFMs) are suited for precise measurement of flow ranges between 5...100 mg/h and 0,1...2 g/h at operating pressures up to 400 bar. The LFM consists of a thermal mass flow sensor and a microprocessor based pc-board with signal and fieldbus conversion and a PID controller for optional mass flow control by means of a separately mounted control valve.

μ-FLOW series are equipped with a digital pc-board, offering high accuracy, excellent temperature stability and fast response. The main digital pc-board contains all of the general functions needed for measurement and control. In addition to the standard RS232 output the instruments also offer analog I/O. As an option, an on-board interface can be mounted to provide DeviceNet™, PROFIBUS DP, Modbus or FLOW-BUS protocols.

Technical specifications

Measurement system

Flow range, based on H ₂ O (intermediate ranges available)	min. 5...100 mg/h max. 0,1...2 g/h
Accuracy (incl. linearity) (based on actual calibration)	±2% FS
Turndown	1:20 (5...100%)
Repeatability	< 0,2% FS (typical H ₂ O)
Operating temperature	5...50°C
Temperature sensitivity	±0,2% FS/°C
Attitude sensitivity	negligible
Warm-up time	approx. 10 min. for accuracy ± 2% FS

Mechanical parts

Material (wetted parts)	stainless steel 316L/320; others on request
Pressure rating	400 bar abs
Process connections	1/16" or 1/8" OD compression type; other on request (<1 g/h we advise to use 1/16" only)
Seals	Metal
Ingress protection (housing)	IP40

Electrical properties

Power supply	+15...24 Vdc +/-10%		
Max. power consumption (meter only)	Supply	at voltage I/O	at current I/O
	15 V	100 mA	120 mA
	24 V	65 mA	85 mA
PROFIBUS DP	add 53 mA (15 V supply) or 30 mA (24 V supply)		
DeviceNet™	add 48 mA (24 V supply)		
Analog output	0...5 (10) Vdc or 0 (4)...20 mA (sourcing output)		
Digital communication	standard: RS232; options: PROFIBUS DP, DeviceNet™, Modbus RTU or ASCII, FLOW-BUS		

Electrical connection

Analog/RS232	9-pin D-connector (male)
PROFIBUS DP	bus: 9-pin D-connector (female); power: 9-pin D-connector (male)
Devicenet™	5-pin M12-connector (male)
FLOW-BUS/Modbus-RTU/ASCII	RJ45 modular jack

Recommended accessories



E-8000 - DIGITAL READOUT / CONTROL SYSTEMS

Bright, wide angle, 1.8" display (TFT technology)
User friendly operation, menu driven with 4 push buttons



BRIGHT - COMPACT LOCAL READOUT/CONTROL MODULE

Bright, wide angle, 1.8" display
User friendly operation
Indication/operation/configuration



PIPS - PLUG-IN POWER SUPPLY

For lab-style or industrial devices
Interchangeable plugs (Euro, UK, USA, Australian, IEC) for mains connection

Related products



μ-FLOW L01V12

Min. flow 5 ... 100 mg/h
Max. flow 0,1 ... 2 g/h
Pressure rating 100 bar
Compact unit; small internal volume
Analog, RS232 or fieldbus I/O



LIQUI-FLOW™ L13

Min. flow 0,25 ... 5 g/h
Max. flow 5 ... 100 g/h
Pressure rating 100 bar
Compact, IP40 design
Analog, RS232 or fieldbus I/O



BRONKHORST HIGH-TECH B.V.

Nijverheidsstraat 1A

NL-7261 AK Ruurlo (NL)

Tel. +31 573 45 88 00

info@bronkhorst.com