

IN-PRESS P-512CI

Digital Electronic Pressure Meter, Industrial Style

- For absolute or gauge pressure
- High accuracy and repeatability
- Well proven, compact thru-flow design
- Rugged, weatherproof housing (IP65, dust and waterproof)
- On-board PID controller for pressure control
- Analog, RS232 and fieldbus communication



Digital Electronic Pressure Meters, Industrial Style

Bronkhorst® model P-512CI Electronic Pressure Transducers (EPTs) are suited for precise measurement of pressure ranges between 1,28...64 bar and 2...100 bar absolute or gauge. The EPT has a well-proven compact thru-flow design and includes a diaphragm type piezo-resistive pressure sensor, a microprocessor based pc-board with signal and fieldbus conversion and a PID controller for optional pressure control by means of a separately mounted control valve. The IN-PRESS model is of rugged design (IP65) for use in industrial environments or even Zone 2 hazardous areas, with optional ATEX Cat. 3 approval.

IN-PRESS series are equipped with a digital pc-board, offering high accuracy, excellent temperature stability and fast response. The main digital pc-board contains all of the general functions needed for measurement and control. In addition to the standard RS232 output the instruments also offer analog I/O. As an option, an on-board interface can be mounted to provide CANopen®, DeviceNet™, PROFIBUS DP, PROFINET, Modbus RTU/ASCII or FLOW-BUS protocols.

Technical specifications

Measurement / control system

Absolute pressure sensors
 Code: M10A - Ranges (FS): 20 ... 100 bara - P-max: 200 bara
 Code: M40A - Ranges (FS): 100 ... 400 bara - P-max: 500 bara

Accuracy (incl. linearity and hysteresis) ±0,5% FS

Repeatability < 0,1% Rd

Pressure rangeability 1:50 for pressure meter;
 1 : 20 for P2-control; 1 : 5 for P1-control

Response time (sensor) 2 msec

Operating temperature -10...+70°C;
 for ATEX cat. 3 0...50°C

Temperature sensitivity 0,1% FS/°C

Leak integrity, outboard tested < 2 x 10⁻⁹ mbar l/s He

Attitude sensitivity max. error at 90° off horizontal < 0,3 mbar

Warm-up time negligible

Mechanical parts

Material (wetted parts)	stainless steel 316L or comparable
Process connections	compression type or face seal couplings
Seals	standard: Viton [®] ; options: EPDM, Kalrez [®] (FFKM)
Ingress protection (housing)	IP65

Electrical properties

Power supply	+15...24 Vdc		
Max. power consumption meter	Supply	at voltage I/O	at current I/O
	15 V	95 mA	125 mA
	24 V	65 mA	85 mA
Max. power consumption controller	Supply	at voltage I/O	at current I/O
	15 V	290 mA	320 mA
	24 V	200 mA	215 mA
PROFIBUS DP	add 53 mA (15 V supply) or 30 mA (24 V supply)		
DeviceNet™	add 48 mA (24 V supply)		
Analog output/command	0...5 (10) Vdc or 0 (4)...20 mA (sourcing output)		
Digital communication	standard: RS232; options: CANopen [®] , DeviceNet™, PROFIBUS DP, PROFINET, Modbus RTU/ASCII or FLOW-BUS		

Electrical connection

Analog/RS232	8 DIN (male);
PROFIBUS DP	bus: 5-pin M12 (female); power: 8 DIN (male);
PROFINET	bus: 2 x 5-pin M12 (female) (in/out); power: 8 DIN (male);
Devicenet™	5-pin M12 (male);
FLOW-BUS/Modbus-RTU/ASCII	5-pin M12 (male)

Note: The measuring cell of the pressure sensor is separated from the external pressure by a thin, sensitive stainless steel diaphragm, and the sealed off cavity between diaphragm and cell is filled with oil. Since the standard oil filling is flammable, Bronkhorst advises to take precautions when oxygen or any other explosive fluid is used.

Technical specifications subject to change without notice.

For dimensional drawings and hook-up diagrams please visit the [product page](#) on our [website](#)

Recommended accessories



E-8000 SERIES

Digital Readout / Control Systems

Bright, wide angle, 1.8" display (TFT technology)
User friendly operation, menu driven with 4 push buttons



PIPS SERIES

Plug-in Power Supply

For lab-style or industrial devices
Interchangeable plugs (Euro, UK, USA, Australian, IEC) for mains connection

Related products



IN-PRESS P-502CI

Min. pressure 2...100 mbar
Max. pressure 1,28...64 bar
Absolute or gauge pressure
Compact IP65 design



IN-PRESS P-522CI

Min. pressure 2...100 bar
Max. pressure 4...200 bar
Absolute or gauge pressure
Compact IP65 design



IN-PRESS F-0XXAI+P-5X2CI (P2-CONTROL)

Min. pressure 2...100 mbar
Max. pressure 8...400 bar
Absolute or gauge pressure
Compact IP65 design



IN-PRESS P-5X2CI+F-0XXAI (P1-CONTROL)

Min. pressure 2...100 mbar
Max. pressure 8...400 bar
Absolute or gauge pressure
Compact IP65 design



BRONKHORST HIGH-TECH B.V.

Nijverheidsstraat 1A

NL-7261 AK Ruurlo (NL)

Tel. +31 573 45 88 00

info@bronkhorst.com