

A047-VAPOUR OPLOSSING VOOR BEVOCHTIGING

APPLICATION NOTE

CONTROLLED HUMIDIFICATION

A leading UK company specializing in synthetic bone repair materials for orthopaedic and dental applications use Bronkhorst products to perfect their production process. A leader in the research and development of bone graft technologies.

Bronkhorst have supplied Controlled Evaporation Mixing (CEM) systems for humidification of the furnaces that are used for the manufacture of the bone repair product.



Application requirements

The furnace at over 1200 degrees Celsius will produce yellow powder if the water is not added, hence the use of the Controlled Evaporation Mixing system (CEM). The properties will not change just the colour of the powder.

The colour is crucial as yellow powder is rejected by surgeons as they believe it to be inferior quality. Having a consistent white colour therefore is of utmost importance.

Important topics

- Accurate dosing of air constituents
- Documentation of test conditions
- Repeatability
- Compact system

Process solution


Humidification of a furnace

After manufacturing the bone grafting powder it needs to be dried and sintered. The process is carried out in a high temperature furnace with a controlled atmosphere. If the atmosphere is not controlled properly, discolouration of the end product renders it useless for sale and cannot be re-worked. The accurate control of water to the furnace by means of a CEM, with air as the carrier gas, results in a perfect white colour recognised by the doctors using this product. Depending on the furnaces, the flow rate of water is accurately controlled at 42 g/h, 84 g/h or 122 g/h.

A high degree of control is needed for repeatable batch consistency of many years for this high value product.

BRIGHT local readout and control

As an option, the systems can be used in combination with BRIGHT local Readout/Control Modules, to give a better visualisation for the user.



Flow scheme

Recommended Products



CEM EVAPORATOR W-202A

Max. 120 g/h vloeistof;
Max. 10 l/min gas
Drukklasse 100 bar
Zeer stabiele dampstroom
Flexibele gas/vloeistofverhouding



EL-FLOW SELECT F-201AV

Min. flow 0,4...20 l/min
Max. flow 0,6...100 l/min
Drukklasse PN64
Compact design
Hoge nauwkeurigheid en herhaalbaarheid



LIQUI-FLOW™ L13

Min. flow 0,25 ... 5 g/h
Max. flow 5 ... 100 g/h
Pressure rating 100 bar
Compact, IP40 design
Analog, RS232 or fieldbus I/O



BRIGHT SERIES

- Compacte lokale R/C-modules

Bright, wijde hoek, 1.8" display
Gebruiksvriendelijke bediening
Uitlezing/bediening/configuratie

Wilt u meer informatie over flowmeters of -regelaars?

Wilt u het laatste nieuws ontvangen over trends in flow control? Schrijf u in voor onze maandelijkse nieuwsbrief.



BRONKHORST NEDERLAND

Lunet 10c

3905 NW Veenendaal

Tel. +31 (0)318 55 12 80

info@bronkhorst.nl